

## THE UNITED KINGDOM VEHICLE APPROVAL AUTHORITY

COMMUNICATION CONCERNING THE APPROVAL GRANTED<sup>(1)</sup>/ APPROVAL EXTENDED<sup>(1)</sup>/ APPROVAL REFUSED-<sup>(1)</sup>/ APPROVAL WITHDRAWN-<sup>(1)</sup>/ PRODUCTION DEFINITELY DISCONTINUED<sup>(1)</sup> OF A TYPE OF MECHANICAL COUPLING DEVICE OR COMPONENT, PURSUANT TO REGULATION NO 55.01



Approval No: E11 55R-0111231 Correction - 01

Reasons for Correction No: stated in paragraph --17

- 1. Trade name or mark of the device or component: Maypole Ltd
- 2. Manufacturer's name for the type of device or component: MP084 (Silver Finish), MP087 (Black Finish) (Combined Ball and Pin Jaw 2 Bolt Fixing 20.20kn) & MP49484 (Pin)
- Manufacturer's name and address: Maypole Ltd, 162 Clapgate Lane, Birmingham, B32 3DE, United Kingdom
- 4. If applicable, name and address of the manufacturer's representative: Not Applicable
- 5. Alternative supplier's names or trade marks applied to the device or component: Not Applicable
- Name and address of company or body taking responsibility for the conformity of production: Maypole Ltd, 162 Clapgate Lane, Birmingham, B32 3DE, United Kingdom



ŁŌŚ

Authority Agency

19-Feb-18

Vehicle

Certification

- 7. Submitted for approval on : 13 June 2017
- 8. Technical service responsible for conducting approval tests: Vehicle Certification Agency
- 9. Brief description:
- 9.1. Type and class of device or component: A50-X
- 9.2. Characteristic values:

9.2.1.	Primary values:						
	D:	20.2 kN	Dc:	20.2 kN	S:	350 kg	
	U:	N/A tonnes	V:	N/A kN			
	Altern	ative Values					
	D:	N/A kN	Dc:	N/A kN	S:	N/A kg	
	U:	N/A tonnes	V:	N/A kN			

9.3. For Class A mechanical coupling devices or components, including towing brackets:

Vehicle manufacturer's maximum permissible vehicle mass: 5000 kg

Distribution of maximum permissible vehicle mass between the axles:

Axle 1:	Not Applicable kg	Axle 2:	Not Applicable kg
Axle 3:	Not Applicable kg	Axle 4:	Not Applicable kg

Vehicle manufacturer's maximum permissible towable trailer mass: 3500 kg

Vehicle manufacturer's maximum permissible static mass on coupling ball: 350 kg

Maximum mass of the vehicle, with bodywork, in running order, including coolant, oils, fuel, tools and spare wheel (if supplied) but not including driver: Various kg

Loading condition under which the tow ball height of a mechanical coupling device fitted to category  $M_1$  vehicles is to be measured -see paragraph 2 of annex 7, appendix 1: Not Applicable

- 9.4. For class B coupling heads, is the coupling head intended to be fitted to an unbraked O1 trailer: Not Applicable
- 10. Instructions for the attachment of the coupling device or component type to the vehicle and photographs or drawings of the mounting points (see Annex 2, Appendix 1) given by the vehicle manufacturer: See Manufacturer's Documents
- 11. Information on the fitting of any special reinforcing brackets or plates or spacing components necessary for the attachment of the coupling device or component (see Annex 2, Appendix 1. Not Applicable

- 12. Additional information where the use of the coupling device or component is restricted to special types of vehicles see annex 5, paragraph 3.4. Not Applicable
- 13. For Class K hook type couplings, details of the drawbar eyes suitable for use with the particular hook type: Not Applicable
- 14. Date of test report: 11 August 2017
- 15. Number of test report: VST406671 / VC7112
- 16. Approval mark position: See manufacturer's documentation
- 17. Reason(s) for correction of approval: To Correct: Alteration of 'S'-value from 260kg to 350kg
- 18. Approval GRANTED/EXTENDED/REFUSED/WITHDRAWN-
- 19. Place: BRISTOL
- 20. Date: 19 FEBRUARY 2018

) ene. Signature: 21.

D. LAWLOR Head of Technical Standards and Legislation

22. The list of documents deposited with the Administration Service which has granted approval is annexed to this communication and may be obtained on request.

Any remarks: Approval to Supplement 6

