



Dati tecnici Technical data Datos técnicos Données techniques Technische Daten	Voltaggio <i>Voltage</i>	Multivolt 10 – 30 VVC	Temperatura esercizio <i>Working temperature</i>	-20°C
	Connessione <i>Connection</i>	Cavo/cable (v.7600)	IPx	+50°C
		6 way connection (v.7601)	Dimensione <i>Dimension</i>	n.d.
	Materiali <i>Materials</i>	ABS – PMMA - PC	Omologazione <i>Omologation</i>	Approx. 147x 222 x 50 mm ECE E3 xxxxx ECE E3 10R xxxx

		Sinistro <i>Left</i>	Destro <i>Right</i>	Posizione <i>Position</i>	Stop	Direzione <i>Direction</i>	Luce targa <i>Nr Plate light</i>	Retronebbia <i>Fog light</i>	Retromarica <i>Inversion light</i>	Ingombro <i>Side marker</i>	Catadiottro <i>Reflector</i>
7600/4	Connessione via cavo - cable	✓		✓	✓	✓		✓	✓	✓	✓
7600/5			✓	✓	✓	✓		✓	✓	✓	✓
7600/14		✓		✓	✓	✓	✓	✓	✓	✓	✓
7600/15			✓	✓	✓	✓	✓	✓	✓	✓	✓
	6 ways connection	Sinistro <i>Left</i>	Destro <i>Right</i>	Posizione <i>Position</i>	Stop	Direzione <i>Direction</i>	Luce targa <i>Nr Plate light</i>	Retronebbia <i>Fog light</i>	Retromarica <i>Inversion light</i>	Ingombro <i>Side marker</i>	Catadiottro <i>Reflector</i>
7601/4		✓		✓	✓	✓		✓	✓	✓	✓
7601/5			✓	✓	✓	✓		✓	✓	✓	✓
7601/14		✓		✓	✓	✓	✓	✓	✓	✓	✓
7601/15			✓	✓	✓	✓	✓	✓	✓	✓	✓