

MP9581 STRATFORD 'PRO' AIR SUN CANOPY USER GUIDE



Please read & follow this user guide & all safety instructions carefully when using this product.

Keep the user guide for future reference. When passing the product onto others be sure to include all documentation. The user guide is also available on our website: www.maypoleltd.com

MP9581 STRATFORD 'PRO' AIR SUN CANOPY USER GUIDE

GENERAL SAFETY

- Not to be used in strong winds and extreme weather conditions.
- If using stepladders or a platform to set up the Air Sun Canopy you will be working at height & should carefully follow the stepladder / platform manufacturer's safety instructions. You should not attempt to set up this Air Sun Canopy from the ladder but only to use the ladder if required to assist people on the ground.
- **DO NOT drive with this Sun Canopy attached to your vehicle.**

CARE OF YOUR SUNCANOPY

- Allow material to dry completely before storing in the storage bag provided.
- Remove dirt with a soft sponge and warm water. DO NOT use detergent.
- DO NOT expose to sparks, flames or other sources of ignition.
- NOTE – during certain conditions moisture maybe visible on the inside of the material. This is the natural build up of condensation and should not be mistaken for leaking.

CONTENTS

Air Sun Canopy x 1

Side walls x 2

Front wall x1

Webbing Straps x 5

Steel Pegs x 14

Hand pump x 1

Carry Bag x 1

BEFORE USE

Choose a clear site that is flat. Remove any sharp objects from the pitching area which could be dangerous or potentially damage the fabric or puncture the air beams.

NOTE – this Air Sun Canopy is suitable for vehicles with an awning channel height range of 235cm – 250cm.

NOTE – either a 4mm or 6mm awning channel is required to fit this Sun Canopy to your vehicle.

MP9581 STRATFORD 'PRO' AIR SUN CANOPY USER GUIDE

PITCHING INSTRUCTIONS

Remove the Sun Canopy from the carry bag and place flat on the ground. Ensure the dual beading faces the vehicle.

The suncanopy has a 4mm & 6mm dual beading sewn into it. Choose the correct beading size for your awning channel (4mm or 6mm) and slide it into the awning channel on your vehicle.



Locate the air valve on the supporting leg of the Sun Canopy and unscrew the top cap.

Connect the large adaptor to the hand pump. Insert the adaptor into the top cap on the valve. Inflate the air beam to approx. 6-7 PSI. Remove the adaptor from the valve and securely tighten the top cap. **WARNING: WHEN INFLATING; DO NOT EXCEED A PRESSURE OF OVER 7 PSI. IN STRONG SUNLIGHT & IN HOT TEMPERATURES REDUCE THE PRESSURE TO 4-5 PSI.**



MP9581 STRATFORD 'PRO' AIR SUN CANOPY USER GUIDE

The Sun Canopy should now be able to support itself.

Buckle together the sizing strap between each leg to achieve the correct spacing. Peg down each leg at the base:



1 webbing strap can be found at the front of the Sun Canopy and 2 on each side. Securely peg each webbing strap into the ground



It is recommended each peg is driven fully into the ground at an angle of 45 Degrees away from the pegging point.

MP9581 STRATFORD 'PRO' AIR SUN CANOPY USER GUIDE

2 sides walls & 1 front wall is included with the canopy.

Each wall can be attached by inserting the zip at the top of the canopy.



Fully zip each side wall and front wall closed and peg down at the base:



To deflate - unscrew the bottom screw on the air valve. **WARNING – Be aware of sudden loud noise caused by air escaping when deflating.**

S. J. O'Leary

Technical Manager Maypole Ltd Nov 2024

Email: sales@maypoleltd.co.uk

Web: www.maypoleltd.com

Maypole Ltd, 162 Clapgate Lane, Birmingham, B32 3DE, UK

Maypole Touring Ireland Ltd, 40 Mespil Road, Dublin 4, D04 C2N4, Ireland