Maypole Car Covers

Fitting Instructions:

- Ensure that all aerials are fully retracted
- Allow car to cool before fitting the cover
- Pull the cover over the car and fit elasticated hems under front and rear bumpers
- Tighten adjustable straps as required

WARNING:

- Should not be fitted during high winds
- Do not fit to a wet or a recently re-painted vehicle
- When fitted for long periods it is recommended that a cloth under sheet be used
- Do not fit the cover over recently painted, repaired or refinished surfaces until the applicable coating or repair has fully cured

WARNINGS FOR USE IN HOT CLIMATES:

Exercise caution when using the cover in hot weather or during prolonged periods of direct sunlight. High temperatures may develop around the vehicle's exterior surfaces, particularly where ventilation is restricted.

Certain vehicle components, including plastic, acrylic, GRP and painted or bonded panels, may be susceptible to heat-related distortion, discolouration or surface damage under extreme conditions.

Avoid leaving the cover fitted for prolonged periods during exceptionally hot, sunny weather. Where possible, position the vehicle in a shaded location and periodically remove the cover to inspect and ventilate the vehicle.

Ensure that the vehicle is suitable for use with an external cover, particularly where it incorporates temperature-sensitive panels, windows, rooflights or other fittings. Refer to the vehicle manufacturer's recommendations where applicable.

Although the cover is manufactured from breathable material, this does not prevent all heat accumulation or guarantee temperature control beneath the cover.

Please be careful using any cover on matte paint in extreme heat as they can be susceptible to marking.

For assistance and all enquiries please contact your local stockist. Alternatively, please email sales@maypoleltd.co.uk

See our complete range at www.maypoleltd.com

Maypole Ltd. Birmingham, UK **Nov 2026**